

(LHD) HINO 300 3711 SC CHASIS 4.0D MT MY2024 - WHITE

VEHICLE CODE: L3711SC4.0D_2

TECHNICAL FEATURES

Engine

Model: HINO N04C-WF

Maximum Power: 85 Kw {116ps} At 2,500 R/Min (JIS Gross)

81 Kw {110 Ps} At 2,500 R/Min (Iso Net)

324 Nm {33 Kgfm} At 1,600 R/Min (JIS Gross) Maximum Torque:

314 Nm {32 Kgfm} At 1,600 R/Min (Iso Net)

Maximum Engine Speed: 3,000 R/Min

Type: Diesel, Turbocharged and Intercooled, 4-Cycle, In-Line

4-Cylinder, Overhead Valve, Water-Cooled

Compression Ignition, Four Stroke Combustion System:

Bore x Stroke: 104 x 118 mm

4.009 L Piston Displacement: Compression Ratio: 18.0: 1 9.4 L Engine Oil Capacity:

Fuel Injection Pump: Electronic Control Common Rail Type with Altitude

Compensation











www.milele.com (#)

Air Cleaner And Intake: Behind Cab Mounted Half-Height Snorkel Air Intake

With Air

Filter, Dry Paper Element

Exhaust Tail: Short Tail Type

Engine Revolution Control: Yes (Instrument Panel Mounted Rotary Knob Type)

Clutch

Type: Dry Single Plate with Damper Springs, Facing Outside

Diameter

300 Mm, Automatic Gap Adjuster

Transmission

Model: RE50, Manual 5-Speeds, With Overdrive

Transmission Shift Lever: Folding Type

Propeller Shaft

Tube Outside Diameter X Thickness: 82.6 X 2.3 Mm

FRONT AXLE

Type: Reversed Elliot, " I " Section Beam

REAR AXLE

Type: Full-Floating, Single Reduction, Single Speed By Hypoid

Gearings

Service Brake:

Front Wheel Brake: Drum Inside Diameter 320 Mm, Lining Width 100 Mm Rear Wheel Brake: Drum Inside Diameter 320 Mm, Lining Width 115 Mm

Exhaust Brake

LSPV (Load Sensing Proportional Valve)

Parking Brake

Type: Mechanical, Internal Expanding Acting on Transmission

Output Shaft, Not Folding Lever

Steering

Type: Telescopic and Tilt Steering Column, Recirculating Ball

Integral Power Steering

Front Suspension

Type: Semi-Elliptic Leaf Springs with Double Acting Shock

Absorbers













Rear Suspension

Semi-Elliptic Main and Auxiliary Leaf Spring with Double Type:

> Acting Shock Absorbers Semi-Elliptic Main and Auxiliary Leaf Spring (Reinforced Type) With Double Acting Shock

Absorbers- Optional

Wheel and Tire

Tire Size: Front and Rear: 7.50r16 10pr, Rib Type Tread (16 X 6.00gs Wheel)

Spare Tire Carrier

Fuel Tank

Capacity: 100 L

Fuel Filter: Primary (With Water Separator) And Secondary Filter

Fuel Filler: Small-Diameter Neck

Chassis Frame

Type: Ladder-Shaped Channel Section Side Rails

Rear Frame Width: 750 Mm

Max. Section (Depth X Flange X Thickness): 192.8 X 65 X 5.9 Mm

Tensile Strength: 540 N/Mm2 (55 Kgf/Mm2) Front Bumper: Dark Grey Type (Resin)

Front Underrun Protector

Tow Hook: Front

CAB

Type: Forward Control, All Steel Welded Construction, High Roof

Front Windshield: **Heat-Absorbing Laminated Glass**

Front Seat: 4-Way Adjustable Driver Seat, Fixed Back Passenger Seat

Integrated Type

Seat Cover: Vinyl Type

Front Seat Belt: 3-Point ELR (Emergency Locking Retractor) Belt on Driver

And Outer Passenger Seat, 2-Point NR (Non-Retractor) Belt

On Centre Passenger Seat

Floor Mat: Vinyl Type Sun Visor: Yes (Both Sides)

Cab trim (quarter panel): Semi trim Instrument panel centre cluster: Dark grey color

Door pocket: Yes (both side)

Seat back pocket: Yes (pocket for driver seat) Grab handle (interior): Yes (driver 1 + passenger 1) Outside rear view mirrors: Convex type, long stay

Inside mirror

2-speed with wash and intermittent feature Windshield wiper:

Front heater and defroster: Yes (with warm up switch)

Car audio: AM/FM radio with USB, AUX. Bluetooth (2 speakers) -


Optional













+971504996459 🙈 info@milele.com 🝙



Room Light: Yes (Reading Light Only)

Door Courtesy Switch: Driver Side

Cigar Lighter Cup Holder Tool Set

Hydraulic Jack

Radiator Grille: Cab Coloured Type

INSTRUMENTS

Speedometer: Yes (Km/H)

Multi-Information

Tachometer: Yes (R/Min)

Coolant Temperature Gauge: Yes (With Buzzer)

Fuel Gauge

Brake Warning: Brake Fluid Level and Vacuum Pressure Warning Lamp And

Buzzer

ELECTRICAL EQUIPMENT

System Voltage: 24V

Batteries: 60 Ah {216 Kc} At 20-Hourrate

Alternator: 24 V, 60A
Starter: 24 V, 4.5 Kw
Headlight: Halogen Type
Headlight Levelling: Manual Type

Position Light

Turn Signal Light (Front)

Stop, Turn, Taillight: Yes (EC Type)
Back-Up Buzzer: Yes - Optional

Diagnoses Connector

Horn: Electric Type, Single

































































